

audiomini

Digital Audiometer



Salient Features

- Brand: Labat
- Value for money
- Durable & Portable

► Tests

- Pure Tone
- BC
- Live Voice
- TDT
- Free Field

► Frequency Range

- AC: 125 Hz to 8000 Hz
- BC: 250 Hz to 8000 Hz

► Maximum Output Level (dB HL)

Frequency	125	250	500	1k	2k	3k	4k	6k	8k		
AC	80	105	115	120	120	120	120	120	105		
BC		40	60	65	75	70	70	40	40		

► audiomini version's

Versions	AC Transducer	BC Transducer
V 1.0	LT 10	LB 70
V 4.0	TDH 39	B 71

► Intensity Range

- Air Conduction: -10 dB HL to +120 dB HL
- Bone Conduction: -10 dB HL to +75 dB HL

► Signal Mode

- Normal ON, OFF
- Masking - White Noise
- Continuous
- Pulsed (2.5 Hz, 50%, 200+200 mS)

► Specifications

- Power Supply: 220V, 50Hz
- Harmonic Distortion < 1%

► Standard Accessories

- LT-10 Headphone
- LB 70 (Bone Vibrator)
- Patient Response Switch
- Calibration Certificate
- Power Adaptor

► Optional Accessories

- TDH39 Headphones
- Radioear B71 (Bone Vibrator)
- Free Field Speakers

► Mechanical

- Weight: 650 gm
- Dimensions: 28 x 16 x 5.5 cm

► Standards & Certifications

- ISO 9001:2015
- ISO 13485:2016
- CDSCO Approved
- Authorized GeM OEM
- ZED Certificate
- RoHS Compliance
- IEC 60601-1:2005 + AMD:2012 Ed:3.1

Note:

*Available optionally at additional price

#For more technical and hardware specifications contact: sales@labatasia.com

~ Specifications and features can be changed without prior notice

Ref. No.: MKT/PM/03 Issue No.: 01 Issue Date: 11/06/2020 Rev No.: 08 Rev Date: 22.01.2026

Hearsound Technology LLP

No.15,1st Floor , P V Rajamannar Salai ,
Vijayaraghapuram,Chennai
Tamil Nadu 600093 India



<https://www.hearsound.shop/>



+91 93853 80920



info@hearsound.in